

USER MANUAL

MINI 1x4 HDMI Splitter

Model No: HDST-S0104M

Enjoy the vivid world !



Seconn International Enterprise Co., Ltd.

Tel No.: 886-2-2221-9011 Fax No.: 886-2-2228-8096
<http://www.seconn-co.com>

INTRODUCTION

Dear customer

Thank you for purchasing this product. For optimum performance and safety, please read these instructions carefully before connecting, operating or adjusting this product. Please keep this manual for future reference.

Our series of HDMI splitters, switchers, extenders, matrixes and converters are designed to make your A/V device use more convenient, more comfortable, more productive and more cost-efficient.

The 1x4 HDMI Splitter use a single HDMI source, accessing to multiple HDMI sinks. The Splitter allows one HDMI devices to be split easily to four HDMI compatible monitors or projectors. The Splitter can also be placed at the end of a long HDMI cable to regenerate the HDMI signal.

Our devices offers solutions for noise, space and security concerns, data center control, information distribution, conference room presentation, school and corporate training environments.

FEATURES

- One HDMI 1.3 input signal split to four HDMI 1.3 sink devices
- HDCP 1.2 protocol compliant
- Support CEC
- Support deep color 30bit, 36bit
- Support Blue-Ray 24/50/60fs/HD-DVD/xvYCC
- Digital audio format, as DTS-HD/Dolby-trueHD/LPCM7.1/DTS/Dolby-AC3/DSD
- Support signal retiming
- Support input up to 15metres AWG26 HDMI 1.3 standard cable length,
output up to 25metres AWG26 cable length
- No loss of quality
- Installs in minutes
- Need DC5V/1.4A power supply

CONNECTING AND OPERATING

1. Connect one cable from HDMI source devices into HDMI Splitter input.
2. Connect one cable from each display (monitor or projector) into the HDMI Splitter outputs.
3. Connect 5V power supply to the HDMI 1x4 Splitter.

SPECIFICATIONS:

HDST-S0104M

HDMI version.....	HDMI 1.3
HDCP version.....	HDCP1.2
HDMI resolution	24/50/60fs/1080p/1080i/720p/576p/576i/480p/480i
Support video color format	24bit/deep color 30bit,36bit
Support audio format.....	DTS-HD/Dolby-trueHD/LPCM7.1/DTS/Dolby-AC3/DSD
Max transmission bandwidth.....	10.2Gbps
Input/Output TMDS signal	0.5~1.5Volts p-p
Input/Output DDC signal	5Volts p-p (TTL)
Input cable distance.....	≤15m HDMI AWG26
Output cable distance.....	≤25m AWG26 HDMI 1.3 standard cable
Max working current.....	600mA
Power adapter format..Input:	AC (50HZ, 60HZ) 100V-240V; Output: DC5V/1.4A
Operating Temperature range.....	(-15 to +55℃)
Operating Humidity range.....	5 to 90%RH (No Condensation)
Dimension (L x W x H)	115x60x24 (mm)
Weight.....	475g