

ROHS

**Recommended
P.C. Board Hole Layout**

Specifications

Current Rating : 3 Amps
Insulator Resistance : 1000 Megohms min.
Contact Resistance : 20 m ohms max.
Dielectric Withstanding : AC 600V
Operating Temperature : -40°C ~ +105°C
Contact Material : Phosphor Bronze
Insulator Material : Polyester, UL 94V-0 P.B.T.
Contact Plated : See Option
Standard: Full Gold Flash

Contact Plating Option	Full Gold Plating	Gold Plating On Contact Area Tin Plating On Solder Area	Full Tin Plating
	GA : Gold Flash GC : Gold 10u" GD : Gold 15u" GE : Gold 30u"	SA : Gold Flash SC : Gold 10u" SD : Gold 15u" SE : Gold 30u"	TA : Tin 100u"

UNIT	mm	Projection		Secom International Enterprise Co., Ltd.			
TOLERANCES				TITLE			
x. = ± 0.5 Angle .x = ± 0.2 X° = 5° .xx = ± 0.10 X° = 2° .XX° = ± 1°				2.54mm Female Header straight, Dual Row type			
				PART NO.		SFHS-2514-2xx2GA	
DRAWN	Kevin	DATE	2009/11/10				
SCALE	3:1	SIZE	A4	SHEET	1/1	REV	A1