



PIN OUT

CN1 (568B)		CN2 (568B)	
WHITE	1	WHITE	1
ORANGE	2	ORANGE	2
RED	3	RED	3
GREEN	6	GREEN	6
BLUE	4	BLUE	4
WHITE	5	WHITE	5
WHITE	7	WHITE	7
BROWN	8	BROWN	8
SHELL		SHELL	
BRAID			

NOTE:

- Electrical test:
 - 100% open short & miss wire test;
 - Insulation resistance:DC 300V 3MΩ;
 - Contact resistance:3Ω;
- RoHS compliant
- MARKING: CAT7 S-STP 600MHz 4PAIRS STRANDED
AWG26 100Ω Halogenfree

MATERIAL LIST:

					Seconn International Enterprise Co., Ltd.					
NO.	PARTS NAME	SPECIFICATION DESCRIPTION	QT'Y	REMARK	DRAW NO.	PRODUCT NAME	CUSTOMER	VIEW	UNT	MM
③	CABLE	Cat. 7 (7/0.16BC*1P+A)*4 SSTP B=0.12mm/80AL-MG JACKET:HF/ORANGE OD:6.5mm	1		FF0020	CAT.7 SSTP 8P8C - 8P8C				
②	OUTER MOLD	75A PVC UL 80°C (UL94-V2), COLOR:ORANGE	2							
①	8P8C PLUG	RJ45 8P8CS, Double stent, CAT. 6A Pin PLATED GOLD 3U", ALL SHELL PLATED NICKEL, Circle Type.	2							
					APPOBY	CHECKBY	DRAWNBY	UNT	MM	
							Ation	Page	1	of 1