



UL20624 / RoHS Compliant

P	T.L.	W	SP	M	T	S1 S2	S3	S4	A	No. of Conductor
1.0	60.0	21.0	19.0	1.0	0.3	4	9	9	0.5	20
+/-0.1	+/-2.0	+/-0.07	+/-0.07	+/-0.1	+/-0.03	+/-1.0	+/-2.0	+/-2.0	LESS THAN	
CONDUCTOR SPECIFICATION	TIN PLATED FLAT COPPER WIRE PLATING	THICKNESS (Ct)		0.05	+/-0.01	WIDTH (Cw)		0.65	+/-0.03	
		THICKNESS : 2.5u								

P x C x I.L x Type (S1/S2/S3) x (Ct x Cw)

|
 PITCH
 |
 Inner Length
 |
 Conductor Length
 |
 Conductor Thickness
 |
 NO of Conductor
 |
 Contact Type
 |
 Supporter tape Length
 |
 Width

Seconn International Enterprise Co., Ltd.

TOLERANCES		PROJECTION	TITLE			
AS DRAWING			FFC Cable 1.0mm Pitch 20 pin L: 60mm UL20624 C(4/4/9/9) (0.05x0.65)			
		UNIT mm				
DRAWN	Kevin	DATE	2020/03/13	PART NO.	SFFC-1020L60C49	
SCALE	NONE	SIZE	A4	SHEET	1/1	REV A1